

LC OPTICAL PATCH-CORD

SINGEL MODE SN: JM-SL-U-X

MULTI MODE SN: JM-OM3-X

MULTI MODE SN: JM-OM4-X

***X = Length**



JM-SL-U-X



JM-OM3-X



JM-OM4-X

Applications

- * Gigabit Ethernet
- * Telecommunication networks
- * Active device termination
- * Video
- * Industrial
- * Multimedia
- * Military
- * Premise installations

Features

- * High temperature stability
- * Good exchangeability
- * Good Durability
- * Low insertion loss and back reflection loss
- * Standard: Telcordia GR-326-CORE

Availability

- * Simlex/Duplex patch-cord available
- * LC/PC & LC/APC patch-cord available
- * Pigtail available
- * Various boot (cable) sizes available
- * Diameter 1mm

	Single mode O52	Multi Mode OM3	Multi Mode OM4
Insertion Loss	Typical $\leq$ 0.2dB, Maximum $\leq$ 0.3dB	$\leq$ 0.25 dB	$\leq$ 0.25 dB
Repeatability	$\geq$ 50 dB (UPC)	$\geq$ 30dB	$\geq$ 30dB
Durability	$\geq$ 60 dB (UPC)		
Interchangeability	$\leq$ 0.1		
Tensile strength	$\leq$ 0.2 dB typical change,1000 matings		
Operating Temperature	$\leq$ 0.2 dB		
	$>$ 70N		
	t -20 to +70°C		

nnect